

**Silicon N-Channel Power MOSFET****General Description:**

HMF18N50, the silicon N-channel Enhanced VDMOSFET, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-220F, which accords with the RoHS standard.


V <sub>DSS</sub>	500	V
I <sub>D</sub>	18	A
P <sub>D</sub> (T <sub>C</sub> =25°C)	70	W
R <sub>DS(ON),TYP.</sub>	0.265	Ω

**Features:**

- Fast Switching
- Low ON Resistance( $R_{dson} \leq 0.31\Omega$ )
- Low Gate Charge
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test

**Applications:**

- Power switch circuit of adaptor and charger

**Absolute (T<sub>C</sub>=25°C unless otherwise specified):**

Symbol	Parameter	Rating	Units
V <sub>DSS</sub>	Drain-to-Source Voltage	500	V
I <sub>D</sub>	Continuous Drain Current	18	A
I <sub>DM<sup>a1</sup></sub>	Pulsed Drain Current	72	A
V <sub>GS</sub>	Gate-to-Source Voltage	±30	V
E <sub>As<sup>a2</sup></sub>	Single Pulse Avalanche Energy	1400	mJ
P <sub>D</sub>	Power Dissipation	70	W
	Derating Factor above 25°C	0.56	W/°C
T <sub>J</sub> , T <sub>stg</sub>	Operating Junction and Storage Temperature Range	150, -55 to 150	°C
T <sub>L</sub>	Maximum Temperature for Soldering	300	°C

Caution Stresses greater than those in the "Absolute Maximum Ratings" may cause permanent damage to the device

### Thermal Characteristics

Symbol	Parameter	Rating	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.79	°C / W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	100	°C / W

### Electrical Characteristics (T<sub>c</sub> = 25°C unless otherwise specified):

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$V_{DSS}$	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	500	--	--	V
$\Delta V_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	$I_D=250\mu A$ , Reference 25°C	--	0.55	--	V/°C
$I_{DSS}$	Drain to Source Leakage Current	$V_{DS}=500V, V_{GS}=0V, T_a=25^{\circ}C$	--	--	1.0	$\mu A$
		$V_{DS}=400V, V_{GS}=0V, T_a=125^{\circ}C$	--	--	100	
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+30V$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-30V$	--	--	-100	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10V, I_D=9A$	--	0.265	0.31	Ω
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	--	4.0	V
$g_{fs}$	Forward Trans conductance	$V_{DS}=15V, I_D=18A$	--	14	--	S

Pulse width < 380μs; duty cycle < 2%.

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=25V$ $f=1.0MHz$	--	2430	--	pF
$C_{oss}$	Output Capacitance		--	236	--	
$C_{rss}$	Reverse Transfer Capacitance		--	25	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D=18A, V_{DD}=250V$ $V_{GS}=10V, R_g=6.1\Omega$	--	15	--	ns
$t_r$	Rise Time		--	30	--	
$t_{d(OFF)}$	Turn-Off Delay Time		--	50	--	
$t_f$	Fall Time		--	40	--	
$Q_g$	Total Gate Charge	$I_D=18A, V_{DD}=250V$ $V_{GS}=10V$	--	52	--	nC
$Q_{gs}$	Gate to Source Charge		--	13	--	
$Q_{gd}$	Gate to Drain ( "Miller" )Charge		--	20	--	


**Source-Drain Diode Characteristics**

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$I_{SD}$	Continuous Source Current (Body Diode)		--	--	18	A
$I_{SM}$	Maximum Pulsed Current (Body Diode)		--	--	72	A
$V_{SD}$	Diode Forward Voltage	$I_S=18A, V_{GS}=0V$	--	--	1.5	V
$t_{rr}$	Reverse Recovery Time	$I_S=18A, T_j=25^\circ C$	--	592	--	ns
$Q_{rr}$	Reverse Recovery Charge	$dI_F/dt=100A/\mu s, V_{GS}=0V$	--	4.7	--	$\mu C$


a1: Repetitive rating; pulse width limited by maximum junction temperature

a2:  $L=10mH$ ,  $I_D=18A$ , Start  $T_j=25^\circ C$


### Characteristics Curve:




**Figure 2. Maximum Power Dissipation vs Case Temperature**




**Figure 4. Typical Output Characteristics**




**Figure 3. Maximum Continuous Drain Current vs Case Temperature**



**Figure 5. Typical Drain-to-Source ON Resistance vs Gate Voltage and Drain Current**



**Figure 6. Maximum Peak Current Capability**



**Figure 7. Typical Transfer Characteristics**





Figure 9. Typical Drain-to-Source ON Resistance vs Drain Current



**Figure 8. Unclamped Inductive Switching Capability**




Figure 10. Typical Drain-to-Source ON Resistance vs Junction Temperature

